



Model No : RP - 05 CENTRE DEMOULDING SYSTEM

[Send Inquiry](#)

Technical Specification :

Features	Machine Specification
Maximum High Pressure	70 Tonnage
Total Power Required	8.5 HP (Three Phase)
Oil Tank Capacity	200 Liters
Manufacturing Capacity	Paver Block 40 MM 100 MM
Production Capacity	Paver Blocks 2500 To 3000 NOS / 8 Hours. Fly Ash Bricks 2500 To 3200 NOS / 8 Hours.
Facility	<ul style="list-style-type: none"> > Centre Demoulding system. > Superior vibration and pressing systems for maximum compaction and strength. > Oil Cooling system Facilitate to cool Down oil even press in working. > Auto Stope control panel. > Self working conditions with Electrical and mechanical Interlock system. > The pressing operation is timer controlled with single switch operation for both pressing and return strokes. ensuring uniform pressure on all sides of paver blocks and tiles.
Paver Blocks	

General Technical Information :

- > Wiper on cylinder top.
- > At a time 4 worker can work.
- > For removing of ring, Facility Of Hydraulic Stand is available.
- > It can also manufacture CHEQUERED TILES, ELEVATION WALL TILES, CABLE TILES.
- > Paver made will have Shining smooth finish.
- > Pavers mfgd. from our PAVER MACHINE are fitted in PETROL (FUEL) PUMP, RAILWAY PLATFORM AIRPORT, SWIMMING POOL, GARDEN RESORT, GENERAL PUBLIC PARKING PLACE, INDUSTRIAL PARKING PLACE RAILWAY CROSSING AND CONTAINER YARD.
- > PAVER MACHINE FACILITATE Mfg. OF paver pc. in two colours : bottom in grey cement material and top pc.(thickness 10 mm) as Required/ selected by customer. this help cost efficiency of paver.