



Model No : RP - 04

### Technical Specification :

Features	Machine Specification
Maximum High Pressure	100 TO 120 Tonnage with vibrator
Total Power Required	28 HP (Three Phase) (Press Machine 10 HP + Pan Mixer 15 HP + Conveyor Belt 2 HP + Vibrator 1 HP)
Oil Tank Capacity	400 Liter ( Hydraulic oil 68 Number )
Facility	Double Feeder facilities for production of interlocking colored paver blocks.
Mixing and Feeding	Pan Mixer with Conveyor Belt
Production	Zik zek Pavers 7000 To 8000 / 8 Hours. I shape Pavers 5000 To 6000 / 8 Hours .
Plastic Pallet Size	23" x 23" Inches, Thickness 18 MM
Accessories with plant	Press Machine - Power Pack - PLC panel Bord -Two Pan Mixer - Conveyor belt - Two Trolley - Brick conveying Reil - Tool Box.
Raw Material	Cement, Sand, Aggeregate, Powder, color etc...
Labours	8 Skilled -1 Skilled
Note	Also Produce Fly Ash Brick Size :230 x 110 x 75 MM 11000 TO 12000/8 Hours

### General Technical Information :

- › Wiper on cylinder top.
- › At a time 4 worker can work.
- › For removing of ring, Facility Of Hydraulic Stand is available.
- › It can also manufacture CHEQUERED TILES, ELEVATION WALL TILES, CABLE TILES.
- › Paver made will have Shining smooth finish.
- › Pavers mfgd. from our PAVER MACHINE are fitted in PETROL (FUEL) PUMP, RAILWAY PLATEFORM AIRPORT, SWIMMING POOL, GARDEN RESORT, GENERAL PUBLIC PARKING PLACE, INDUSTRIAL PARKING PLACE RAILWAY CROSSING AND CONTAINER YARD.
- › PAVER MACHINE FACILITATE Mfg. OF paver pc. in two colours : bottom in grey cement material and top pc.( thickness 10 mm ) as Required/ selected by customer. this help cost efficiency of paver.