



Model No : RP - 105

Technical Specification :

Features	Machine Specification
Maximum High Pressure	80 Tonnage
Total Power Required	10 HP (Three Phase)
Oil Tank Capacity	400 Ltr. (Hydraulic Oil 68 Number)
Facility	Double feeder facilitates for production of Interlocking colored paver blocks.
Mixing and Feeding	Pan Mixer and Manual OR Conveyor Belt.
Production	Paver Blocks 2000 To 2500 / 8 Hours.
Accessories with plant	Press Machine - Power Pack - PLC Panel Board - Tool Box.
Raw Material	Cement - Sand - Aggregate powder color Etc..
Labours	2 unskilled - 1 skilled
Note	Also produce Fly-Ash-Bricks

General Technical Information :

- › Piston is Hard Chrome
- › Wiper on cylinder top.
- › At a time 4 worker can work.
- › For removing of ring, Facility Of Hydraulic Stand is available.
- › It can also manufacture CHEQUERED TILES, ELEVATION WALL TILES.
- › Paver made will have Shining smooth finish.
- › Pavers mfgd. from our PAVER MACHINE are fitted in PETROL (FUEL) PUMP, RAILWAY PLATFORM, AIRPORT, SWIMMING POOL, GARDEN RESORT, GENERAL PUBLIC PARKING PLACE, INDUSTRIAL PARKING PLACE RAILWAY CROSSING AND CONTAINER YARD.
- › PAVER MACHINE FACILITATE Mfg. OF paver pc. in two colours : bottom in grey cement material and top pc.(thickness 10 mm) as Required/ selected by customer. this help cost efficiency of paver.