



Model No : RP-03

### Technical Specification :

Features	Machine Specification
Maximum High Pressure	70 Tonnage with vibrator
Total Power Required	6 HP ( Three Phase )
Oil Tank Capacity	200 Liters
Manufacturing Capacity	Paver Blocks up to 40 MM to 150 MM Thickness. Kerb Stone 450 × 300 × 150 MM Thickness.
Production Capacity	Paver Block 1800 To 2000 NOS / 8 Hours. Fly Ash Brick 2000 To 2200 NOS / 8 Hours.
Facility	<ul style="list-style-type: none"> <li>› Superior Vibration and Pressing Systems For maximum compaction and strength.</li> <li>› Trolley System Mould moves operators though trolley</li> <li>› Oil Cooling system Facilitate to cool Down oil even press in working.</li> <li>› Auto Stope control panel.</li> <li>› Self working conditions with Electrical and mechanical Interlock system</li> <li>› The pressing operation is timer controlled with single switch operation for both pressing and return strokes ensuring oniform pressure on all sides of paver blocks and tiles.</li> </ul>
Paver Block	

### General Technical Information :

- › Wiper on cylinder top.
- › At a time 4 worker can work.
- › For removing of ring, Facility Of Hydraulic Stand is available.
- › It can also manufacture CHEQUERED TILES, ELEVATION WALL TILES.
- › Paver made will have Shining smooth finish.
- › Pavers mfgd. from our PAVER MACHINE are fitted in PETROL (FUEL) PUMP, RAILWAY PLATFORM AIRPORT, SWIMMING POOL, GARDEN RESORT, GENERAL PUBLIC PARKING PLACE, INDUSTRIAL PARKING PLACE RAILWAY CROSSING AND CONTAINER YARD.
- › PAVER MACHINE FACILITATE Mfg. OF paver pc. in two colours : bottom in grey cement material and top pc.(thickness 10 mm ) as Required/ selected by customer. this help cost efficiency of paver.

